

lenovo

Lenovo G470/G475/ G570/G575

Hardware Maintenance Manual

Note:

Before using this information and the product it supports, be sure to read the general information under "Notices" on page 89.

First Edition (Dec. 2010)

© Copyright Lenovo 2010. All rights reserved.

LENOVO products, data, computer software, and services have been developed exclusively at private expense and are sold to governmental entities as commercial items as defined by 48 C.F.R. 2.101 with limited and restricted rights to use, reproduction and disclosure.

LIMITED AND RESTRICTED RIGHTS NOTICE: If products, data, computer software, or services are delivered pursuant a General Services Administration "GSA" contract, use, reproduction, or disclosure is subject to restrictions set forth in Contract No. GS-35F-05925.

© 2010 Lenovo

Contents

About this manual	iv	1050 Hard disk drive	38
Safety information	1	1060 DIMM	40
General safety	2	1070 Fan assembly and Heat Sink assembly	41
Electrical safety	3	1080 CPU	44
Safety inspection guide	5	1090 PCI Express Mini Card for wireless LAN	45
Handling devices that are sensitive to electrostatic discharge	6	1100 Keyboard	47
Grounding requirements	6	1110 Keyboard bezel	49
Safety notices: multilingual translations	7	1120 Power board and touch inductive panel	52
Laser compliance statement	14	1130 System board	53
Important service information	16	1140 LCD unit	56
Strategy for replacing FRUs	16	1150 Speakers, bluetooth daughter card and base cover	59
Strategy for replacing a hard disk drive	17	1160 LCD front bezel	64
Important notice for replacing a system board	17	1170 LCD panel and hinges	65
Important information about replacing RoHS compliant FRUs	18	1180 Integrated camera	67
General checkout	19	1190 Antenna assembly and LCD cover	68
What to do first	20	Locations	69
Power system checkout	21	Front view	69
Checking the AC adapter	21	Right-side view	70
Checking operational charging	21	Bottom and Left-side view	70
Checking the battery pack	22	Parts list	71
Related service information	23	Overall	72
Restoring the factory contents by using OneKey Recovery	23	LCD FRUs	77
Restore of factory default	23	Keyboard	79
Using recovery discs	23	Miscellaneous parts	84
Passwords	24	AC adapters	85
Power-on password	24	Power cords	86
Supervisor password	24	Notices	89
Power management	25	Trademarks	90
Screen blank mode	25		
Sleep (standby) mode	25		
Hibernation mode	26		
Lenovo G470/G475/G570/G575	27		
Specifications	27		
Status indicators	29		
Fn key combinations	31		
FRU replacement notices	32		
Screw notices	32		
Removing and replacing an FRU	33		
1010 Battery pack	34		
1020 Dummy cards	35		
1030 Optical drive	36		
1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover	37		

About this manual

This manual contains service and reference information for the following Lenovo product:

Lenovo G470/G475/G570/G575

Use this manual to troubleshoot problems.

The manual is divided into the following sections:

- The common sections provide general information, guidelines, and safety information required for servicing computers.
- The product-specific section includes service, reference, and product-specific parts information.

Important:

This manual is intended only for trained servicers who are familiar with Lenovo products. Use this manual to troubleshoot problems effectively.

Before servicing a Lenovo product, make sure to read all the information under “Safety information” on page 1 and “Important service information” on page 16.

Safety information

This chapter presents the following safety information that you need to get familiar with before you service a Lenovo G470/G475/G570/G575 computer:

- “General safety” on page 2
- “Electrical safety” on page 3
- “Safety inspection guide” on page 5
- “Handling devices that are sensitive to electrostatic discharge” on page 6
- “Grounding requirements” on page 6
- “Safety notices: multilingual translations” on page 7
- “Laser compliance statement” on page 14

General safety

Follow these rules below to ensure general safety:

- Observe a good housekeeping in the area where the machines are put during and after the maintenance.
- When lifting any heavy object:
 1. Make sure that you can stand safely without slipping.
 2. Distribute the weight of the object equally between your feet.
 3. Use a slow lifting force. Never move suddenly or twist when you attempt to lift it.
 4. Lift it by standing or pushing up with your leg muscles; this action could avoid the strain from the muscles in your back. Do not attempt to lift any object that weighs more than 16 kg (35 lb) or that you think is too heavy for you.
- Do not perform any action that causes hazards to the customer, or that makes the machine unsafe.
- Before you start the machine, make sure that other service representatives and the customer are not in a hazardous position.
- Place removed covers and other parts in a safe place, keeping them away from all personnel, while you are servicing the machine.
- Keep your toolcase away from walk areas so that other people will not trip it over.
- Do not wear loose clothing that can be trapped in the moving parts of the machine. Make sure that your sleeves are fastened or rolled up above your elbows. If your hair is long, fasten it.
- Insert the ends of your necktie or scarf inside clothing or fasten it with the nonconductive clip, about 8 centimeters (3 inches) from the end.
- Do not wear jewelry, chains, metal-frame eyeglasses, or metal fasteners for your clothing.

Attention: Metal objects are good electrical conductors.
- Wear safety glasses when you are hammering, drilling, soldering, cutting wire, attaching springs, using solvents, or working in any other conditions that may be hazardous to your eyes.
- After service, reinstall all safety shields, guards, labels, and ground wires. Replace any safety device that is worn or defective.
- Reinstall all covers correctly before returning the machine to the customer.
- Fan louvers on the machine help to prevent the overheating of internal components. Do not obstruct fan louvers or cover them with labels or stickers.

Electrical safety

Observe the following rules when working on electrical equipments.

Important:

Use only approved tools and test equipments. Some hand tools have handles covered with a soft material that does not insulate you when working with live electrical currents.

Many customers have rubber floor mats near their machines that contain small conductive fibers to decrease electrostatic discharges. Do not use such kind of mat to protect yourself from electrical shock.

- Find the room emergency power-off (EPO) switch, disconnecting the switch or electrical outlet. If an electrical accident occurs, you can then operate the switch or unplug the power cord quickly.
- Do not work alone under hazardous conditions or near the equipment that has hazardous voltages.
- Disconnect all power before:
 - Performing a mechanical inspection
 - Working near power supplies
 - Removing or installing main units
- Before you start to work on the machine, unplug the power cord. If you cannot unplug it, ask the customer to power-off the wall box that supplies power to the machine, and to lock the wall box in the off position.
- If you need to work on a machine that has exposed electrical circuits, observe the following precautions:
 - Ensure that another person, familiar with the power-off controls, is near you.

Attention: Another person must be there to switch off the power, if necessary.
 - Use only one hand when working with powered-on electrical equipment; keep the other hand in your pocket or behind your back.

Attention: An electrical shock can occur only when there is a complete circuit. By observing the above rule, you may prevent a current from passing through your body.
 - When using testers, set the controls correctly and use the approved probe leads and accessories for that tester.
 - Stand on suitable rubber mats (obtained locally, if necessary) to insulate you from grounds such as metal floor strips and machine frames.

Observe the special safety precautions when you work with very high voltages; instructions for these precautions are in the safety sections of maintenance information. Be extremely careful when you measure the high voltages.

- Regularly inspect and maintain your electrical hand tools for safe operational condition.
- Do not use worn or broken tools and testers.
- Never assume that power has been disconnected from a circuit. First, check it to make sure that it has been powered off.

- Always look carefully for possible hazards in your work area. Examples of these hazards are moist floors, nongrounded power extension cables, power surges, and missing safety grounds.
- Do not touch live electrical circuits with the reflective surface of a plastic dental mirror. The surface is conductive; such touching can cause personal injury and machine damage.
- Do not service the following parts with the power on when they are removed from their normal operating places in a machine:
 - Power supply units
 - Pumps
 - Blowers and fans
 - Motor generatorsand similar units. (This practice ensures correct grounding of the units.)
- If an electrical accident occurs:
 - Caution: do not become a victim yourself.
 - Switch off the power.
 - Send the victim to get medical aid.

Safety inspection guide

The purpose of this inspection guide is to assist you in identifying potential unsafe conditions. As each machine was designed and built, required safety items were installed to protect users and service personnel from injury. This guide addresses only those items. You should use good judgment to identify potential safety hazards according to the attachment of non-Lenovo features or options not covered by this inspection guide.

If any unsafe conditions are present, you must determine how serious the apparent hazard could be and whether you can continue without first correcting the problem.

Consider these conditions and the safety hazards they present:

- Electrical hazards, especially primary power (primary voltage on the frame can cause serious or fatal electrical shock)
- Explosive hazards, such as a damaged CRT face or a bulging capacitor
- Mechanical hazards, such as loose or missing hardware

To determine whether there are any potential unsafe conditions, use the following checklist at the beginning of every service task. Begin the checks with the power off, and the power cord disconnected.

Checklist:

1. Check exterior covers for damage (loose, broken, or sharp edges).
2. Turn off the computer. Disconnect the power cord.
3. Check the power cord for:
 - a. A third-wire ground connector in good condition. Use a meter to measure third-wire ground continuity for 0.1 ohm or less between the external ground pin and the frame ground.
 - b. The power cord should be the type specified in the parts list.
 - c. Insulation must not be frayed or worn.
4. Check for cracked or bulging batteries.
5. Remove the cover.
6. Check for any obvious non-Lenovo alterations. Use good judgment as to the safety of any non-Lenovo alterations.
7. Check inside the unit for any obvious unsafe conditions, such as metal filings, contamination, water or other liquids, or signs of fire or smoke damage.
8. Check for worn, frayed, or pinched cables.
9. Check that the power-supply cover fasteners (screws or rivets) have not been removed or tampered with.

Handling devices that are sensitive to electrostatic discharge

Any computer part containing transistors or integrated circuits (ICs) should be considered sensitive to electrostatic discharge (ESD). ESD damage can occur when there is a difference in charge between objects. Protect against ESD damage by equalizing the charge so that the machine, the part, the work mat, and the person handling the part are all at the same charge.

Notes:

1. Use product-specific ESD procedures when they exceed the requirements noted here.
2. Make sure that the ESD protective devices you use have been certified (ISO 9000) as fully effective.

When handling ESD-sensitive parts:

- Keep the parts in protective packages until they are inserted into the product.
- Avoid contact with other people.
- Wear a grounded wrist strap against your skin to eliminate static on your body.
- Prevent the part from touching your clothing. Most clothing is insulative and retains a charge even when you are wearing a wrist strap.
- Use the black side of a grounded work mat to provide a static-free work surface. The mat is especially useful when handling ESD-sensitive devices.
- Select a grounding system, such as those listed below, to provide protection that meets the specific service requirement.

Note:

The use of a grounding system to guard against ESD damage is desirable but not necessary.

- Attach the ESD ground clip to any frame ground, ground braid, or green-wire ground.
- When working on a double-insulated or battery-operated system, use an ESD common ground or reference point. You can use coax or connector-outside shells on these systems.
- Use the round ground prong of the ac plug on ac-operated computers.

Grounding requirements

Electrical grounding of the computer is required for operator safety and correct system function. Proper grounding of the electrical outlet can be verified by a certified electrician.

Safety notices: multilingual translations

The safety notices in this section are provided in English, French, German, Hebrew, Italian, Japanese, and Spanish.

Safety notice 1

Before the computer is powered on after FRU replacement, make sure all screws, springs, and other small parts are in place and are not left loose inside the computer. Verify this by shaking the computer and listening for rattling sounds. Metallic parts or metal flakes can cause electrical shorts.

Avant de remettre l'ordinateur sous tension après remplacement d'une unité en clientèle, vérifiez que tous les ressorts, vis et autres pièces sont bien en place et bien fixées. Pour ce faire, secouez l'unité et assurez-vous qu'aucun bruit suspect ne se produit. Des pièces métalliques ou des copeaux de métal pourraient causer un court-circuit.

Bevor nach einem FRU-Austausch der Computer wieder angeschlossen wird, muß sichergestellt werden, daß keine Schrauben, Federn oder andere Kleinteile fehlen oder im Gehäuse vergessen wurden. Der Computer muß geschüttelt und auf Klappergeräusche geprüft werden. Metallteile oder-splitter können Kurzschlüsse erzeugen.

לפני הפעלת המחשב לאחר החלפת FRU יש לוודא שכל הברגים, הקפיצים, וחלקים קטנים אחרים נמצאים במקומם ואינם חופשיים לזוז בתוך המחשב. כדי לוודא זאת, יש לטלטל את המחשב ולחקש לבקש לקולות שקשוק. חלקי או שבבי מתכת עלולים לגרום לקצרים חשמליים.

Prima di accendere l'elaboratore dopo che é stata effettuata la sostituzione di una FRU, accertarsi che tutte le viti, le molle e tutte le altre parti di piccole dimensioni siano nella corretta posizione e non siano sparse all'interno dell'elaboratore. Verificare ciò scuotendo l'elaboratore e prestando attenzione ad eventuali rumori; eventuali parti o pezzetti metallici possono provocare cortocircuiti pericolosi.

FRU の交換後、コンピュータの電源を入れる前に、ねじ、バネ、その他の小さな部品がすべて正しい位置にあり、またコンピュータの内部で緩んでいないことを確認してください。これを確認するには、コンピュータを振って、カチャカチャと音がしないか確かめます。金属部品や金属破片はショートの原因になることがあります。

Antes de encender el sistema despues de sustituir una FRU, compruebe que todos los tornillos, muelles y demás piezas pequeñas se encuentran en su sitio y no se encuentran sueltas dentro del sistema. Compruébelo agitando el sistema y escuchando los posibles ruidos que provocarían. Las piezas metálicas pueden causar cortocircuitos eléctricos.

Safety notice 2

⚠ DANGER

Some standby batteries contain a small amount of nickel and cadmium. Do not disassemble a standby battery, recharge it, throw it into fire or water, or short-circuit it. Dispose of the battery as required by local ordinances or regulations. Use only the battery in the appropriate parts listing. Use of an incorrect battery can result in ignition or explosion of the battery.

Certaines batteries de secours contiennent du nickel et du cadmium. Ne les démontez pas, ne les rechargez pas, ne les exposez ni au feu ni à l'eau. Ne les mettez pas en court-circuit. Pour les mettre au rebut, conformez-vous à la réglementation en vigueur. Lorsque vous remplacez la pile de sauvegarde ou celle de l'horloge temps réel, veillez à n'utiliser que les modèles cités dans la liste de pièces détachées adéquate. Une batterie ou une pile inappropriée risque de prendre feu ou d'exploser.

Die Bereitschaftsbatterie, die sich unter dem Diskettenlaufwerk befindet, kann geringe Mengen Nickel und Cadmium enthalten. Sie darf nicht zerlegt, wiederaufgeladen, kurzgeschlossen, oder Feuer oder Wasser ausgesetzt werden. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Beim Ersetzen der Bereitschafts- oder Systembatterie nur Batterien des Typs verwenden, der in der Ersatzteilliste aufgeführt ist. Der Einsatz falscher Batterien kann zu Entzündung oder Explosion führen.

סוללות המתנה מסוימות מכילות כמות קטנה של ניקל וקדמיום. אין לפרק סוללת המתנה, לטעון אותה מחדש, להשליך אותה לאש או למים או לקצר אותה. יש לסלק את הסוללה בנדרש על ידי התקנות והחוקים המקומיים. יש להשתמש רק בסוללה המופיעה ברשימת החלקים המתאימה. שימוש בסוללה לא מתאימה עלול לגרום להצתה או התפוצצות של הסוללה.

Alcune batterie di riserva contengono una piccola quantità di nichel e cadmio. Non smontarle, ricaricarle, gettarle nel fuoco o nell'acqua né cortocircuitarle. Smaltirle secondo la normativa in vigore (DPR 915/82, successive disposizioni e disposizioni locali). Quando si sostituisce la batteria dell'RTC (real time clock) o la batteria di supporto, utilizzare soltanto i tipi inseriti nell'appropriato Catalogo parti. L'impiego di una batteria non adatta potrebbe determinare l'incendio o l'esplosione della batteria stessa.

予備バッテリーの中には少量のニッケルとカドミウムが含まれているものがあります。したがって、予備バッテリーの分解、再充電、火または水の中への投棄、またはショートさせることは決して行わないでください。バッテリーを廃棄する場合は地方自治体の条例に従ってください。適切なパーツ・リストにあるバッテリーだけを使用してください。誤ったバッテリーを使用すると、バッテリーが発火したり、爆発したりすることがあります。

Algunas baterías de reserva contienen una pequeña cantidad de níquel y cadmio. No las desmonte, ni recargue, ni las eche al fuego o al agua ni las cortocircuite. Deséchelas tal como dispone la normativa local. Utilice sólo baterías que se encuentren en la lista de piezas. La utilización de una batería no apropiada puede provocar la ignición o explosión de la misma.

Safety notice 3**⚠ DANGER**

The battery pack contains small amounts of nickel. Do not disassemble it, throw it into fire or water, or short-circuit it. Dispose of the battery pack as required by local ordinances or regulations. Use only the battery in the appropriate parts listing when replacing the battery pack. Use of an incorrect battery can result in ignition or explosion of the battery.

La batterie contient du nickel. Ne la démontez pas, ne l'exposez ni au feu ni à l'eau. Ne la mettez pas en court-circuit. Pour la mettre au rebut, conformez-vous à la réglementation en vigueur. Lorsque vous remplacez la batterie, veillez à n'utiliser que les modèles cités dans la liste de pièces détachées adéquate. En effet, une batterie inappropriée risque de prendre feu ou d'exploser.

Akkus enthalten geringe Mengen von Nickel. Sie dürfen nicht zerlegt, wiederaufgeladen, kurzgeschlossen, oder Feuer oder Wasser ausgesetzt werden. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Beim Ersetzen der Batterie nur Batterien des Typs verwenden, der in der Ersatzteilliste aufgeführt ist. Der Einsatz falscher Batterien kann zu Entzündung oder Explosion führen.

מארז הסוללה מכיל כמויות קטנות של ניקל
וקדמיום. אין לפרק את מארז הסוללה, להשליך
אותו לאש או למים או לקצר אותו. יש לסלק את
מארז הסוללה הסוללה כנדרש על ידי התקנות
והחוקים המקומיים. יש להשתמש רק בסוללה
המופיעה ברשימת החלקים המתאימה בזמן החלפת
מארז הסוללה. שימוש בסוללה לא מתאימה עלול
לגרום להצתה או התפוצצות של הסוללה.

La batteria contiene piccole quantità di nichel. Non smontarla, gettarla nel fuoco o nell'acqua né cortocircuitarla. Smaltirla secondo la normativa in vigore (DPR 915/82, successive disposizioni e disposizioni locali). Quando si sostituisce la batteria, utilizzare soltanto i tipi inseriti nell'appropriato Catalogo parti. L'impiego di una batteria non adatta potrebbe determinare l'incendio o l'esplosione della batteria stessa.

バッテリー・パックには少量のニッケルが含まれています。バッテリー・パックを分解したり、火または水の中に投げ込んだり、ショートさせないでください。バッテリー・パックの廃棄にあたっては、地方自治体の条例または規則に従ってください。バッテリー・パックを交換するときは、適切なパーツ・リストにあるバッテリーだけを使用してください。誤ったバッテリーを使用すると、バッテリーが発火したり、爆発したりすることがあります。

Las baterías contienen pequeñas cantidades de níquel. No las desmonte, ni recargue, ni las eche al fuego o al agua ni las cortocircuite. Deséchelas tal como dispone la normativa local. Utilice sólo baterías que se encuentren en la lista de piezas al sustituir la batería. La utilización de una batería no apropiada puede provocar la ignición o explosión de la misma.

Safety notice 4

⚠ DANGER

The lithium battery can cause a fire, an explosion, or a severe burn. Do not recharge it, remove its polarized connector, disassemble it, heat it above 100°C (212°F), incinerate it, or expose its cell contents to water. Dispose of the battery as required by local ordinances or regulations. Use only the battery in the appropriate parts listing. Use of an incorrect battery can result in ignition or explosion of the battery.

La pile de sauvegarde contient du lithium. Elle présente des risques d'incendie, d'explosion ou de brûlures graves. Ne la rechargez pas, ne retirez pas son connecteur polarisé et ne la démontez pas. Ne l'exposez pas à une température supérieure à 100°C, ne la faites pas brûler et n'en exposez pas le contenu à l'eau. Mettez la pile au rebut conformément à la réglementation en vigueur. Une pile inappropriée risque de prendre feu ou d'exploser.

Die Systembatterie ist eine Lithiumbatterie. Sie kann sich entzünden, explodieren oder schwere Verbrennungen hervorrufen. Batterien dieses Typs dürfen nicht aufgeladen, zerlegt, über 100 C erhitzt oder verbrannt werden. Auch darf ihr Inhalt nicht mit Wasser in Verbindung gebracht oder der zur richtigen Polung angebrachte Verbindungsstecker entfernt werden. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Beim Ersetzen der Batterie nur Batterien des Typs verwenden, der in der Ersatzteilliste aufgeführt ist. Der Einsatz falscher Batterien kann zu Entzündung oder Explosion führen.

סוללת הליתיום עלולה לגרום לשריפה, להתפוצצות או לכוויות קשות. אין לטעון אותה מחדש, לסלק את המחבר המקוטב שלה, לפרק אותה או לחמם אותה לטמפרטורה העולה על 100 מעלות צלזיוס. אין לשרוף את הסוללה ואין לחשוף את תוכן התא למים. יש לסלק את הסוללה כנדרש בתקנות ובחוקים המקומיים. יש להשתמש רק בסוללה המופיעה ברשימת החלקים המתאימים. שימוש בסוללה אחרת עלול לגרום לסכנת שריפה או התפוצצות.

La batteria di supporto è una batteria al litio e può incendiarsi, esplodere o procurare gravi ustioni. Evitare di ricaricarla, smontarne il connettore polarizzato, smontarla, riscaldarla ad una temperatura superiore ai 100 gradi centigradi, incendiarla o gettarla in acqua. Smaltirla secondo la normativa in vigore (DPR 915/82, successive disposizioni e disposizioni locali). L'impiego di una batteria non adatta potrebbe determinare l'incendio o l'esplosione della batteria stessa.

リチウム・バッテリーは、火災、爆発、または重症のやけどを引き起こすことがあります。バックアップ・バッテリーの充電、その極性コネクタの取り外し、バッテリー本体の分解、100℃(212°F)以上の加熱、焼却、電池の中身を水に浸すことはしないでください。バッテリーを廃棄する場合は地方自治体の条例に従ってください。適切なパーツ・リストにあるバッテリーだけを使用してください。誤ったバッテリーを使用すると、バッテリーが発火したり、爆発したりすることがあります。

La batería de repuesto es una batería de litio y puede provocar incendios, explosiones o quemaduras graves. No la recargue, ni quite el conector polarizado, ni la desmonte, ni caliente por encima de los 100°C (212°F), ni la incinere ni exponga el contenido de sus celdas al agua. Deséchela tal como dispone la normativa local.

Safety notice 5

If the LCD breaks and the fluid from inside the LCD gets into your eyes or on your hands, immediately wash the affected areas with water at least for 15 minutes. Seek medical care if any symptoms caused by the fluid are present after washing.

Si le panneau d'affichage à cristaux liquides se brise et que vous recevez dans les yeux ou sur les mains une partie du fluide, rincez-les abondamment pendant au moins quinze minutes. Consultez un médecin si des symptômes persistent après le lavage.

Die Leuchtstoffröhre im LCD-Bildschirm enthält Quecksilber. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Der LCD-Bildschirm besteht aus Glas und kann zerbrechen, wenn er unsachgemäß behandelt wird oder der Computer auf den Boden fällt. Wenn der Bildschirm beschädigt ist und die darin befindliche Flüssigkeit in Kontakt mit Haut und Augen gerät, sollten die betroffenen Stellen mindestens 15 Minuten mit Wasser abgespült und bei Beschwerden anschließend ein Arzt aufgesucht werden.

אם מסך הגביש הנוזלי (LCD) נשבר והנוזל מתוך המסך בא במגע עם עיניכם או ידיכם, שטפו את האזורים הננועים מיד במים במשך 15 דקות לפחות. פנו לקבלת עזרה רפואית אם תסמינים הנובעים מהמגע עם הנוזל נמשכים לאחר השטיפה.

Nel caso che caso l'LCD si dovesse rompere ed il liquido in esso contenuto entrasse in contatto con gli occhi o le mani, lavare immediatamente le parti interessate con acqua corrente per almeno 15 minuti; poi consultare un medico se i sintomi dovessero permanere.

LCD が破損し、LCD 中の液体が目に入ったり、手に触れたりした場合は、液体が触れた部分を少なくとも 15 分間洗い流してください。洗い流した後に、液体によって何らかの症状が現れた場合は、医師の治療を受けてください。

Si la LCD se rompe y el fluido de su interior entra en contacto con sus ojos o sus manos, lave inmediatamente las áreas afectadas con agua durante 15 minutos como mínimo. Obtenga atención medica si se presenta algún síntoma del fluido despues de lavarse.

Safety notice 6

⚠ DANGER

To avoid shock, do not remove the plastic cover that protects the lower part of the inverter card.

Afin d'éviter tout risque de choc électrique, ne retirez pas le cache en plastique protégeant la partie inférieure de la carte d'alimentation.

Aus Sicherheitsgründen die Kunststoffabdeckung, die den unteren Teil der Spannungswandlerplatine umgibt, nicht entfernen.

כדי למנוע התחשמלות, אין להסיר את מכסה הפלסטיק המגן על חלקו התחתון של הכרטיס ההפוך.

Per evitare scosse elettriche, non rimuovere la copertura in plastica che avvolge la parte inferiore della scheda invertitore.

感電を防ぐため、インバーター・カードの下部を保護しているプラスチック・カバーを外さないでください。

Para evitar descargas, no quite la cubierta de plástico que rodea la parte baja de la tarjeta invertida.

Safety notice 7

⚠ DANGER

Though the main batteries have low voltage, a shorted or grounded battery can produce enough current to burn personnel or combustible materials.

Bien que le voltage des batteries principales soit peu élevé, le court-circuit ou la mise à la masse d'une batterie peut produire suffisamment de courant pour brûler des matériaux combustibles ou causer des brûlures corporelles graves.

Obwohl Hauptbatterien eine niedrige Spannung haben, können sie doch bei Kurzschluß oder Erdung genug Strom abgeben, um brennbare Materialien zu entzünden oder Verletzungen bei Personen hervorzurufen.

אף שהסוללות הראשיות הן בעלות מתח נמוך, סוללה מקוצרת או מוארקת עלולה להפיק זרם מספיק לגרימת כוויות או להצתת חומרים דליקים.

Sebbene le batterie di alimentazione siano a basso voltaggio, una batteria in corto circuito o a massa può fornire corrente sufficiente da bruciare materiali combustibili o provocare ustioni ai tecnici di manutenzione.

メイン・バッテリーの電圧は低くても、ショートしたり、接地したバッテリーが、作業者にやけどを負わせたり、可燃物を燃やすだけの電流を発生させる場合があります。

Aunque las baterías principales tienen un voltaje bajo, una batería cortocircuitada o con contacto a tierra puede producir la corriente suficiente como para quemar material combustible o provocar quemaduras en el personal.

Safety notice 8

DANGER

Before removing any FRU, turn off the computer, unplug all power cords from electrical outlets, remove the battery pack, and then disconnect any interconnecting cables.

Avant de retirer une unité remplaçable en clientèle, mettez le système hors tension, débranchez tous les cordons d'alimentation des socles de prise de courant, retirez la batterie et déconnectez tous les cordons d'interface.

Die Stromzufuhr muß abgeschaltet, alle Stromkabel aus der Steckdose gezogen, der Akku entfernt und alle Verbindungskabel abgenommen sein, bevor eine FRU entfernt wird.

לפני סילוק FRU כלשהו, יש לכבות את המחשב, לנתק את כל כבלי החשמל משקעי החשמל, להוציא את מארז הסוללה, ואז לנתק כבלי חיבור אחרים אם יש כאלה.

Prima di rimuovere qualsiasi FRU, spegnere il sistema, scollegare dalle prese elettriche tutti i cavi di alimentazione, rimuovere la batteria e poi scollegare i cavi di interconnessione.

FRU を取り外す前に、ThinkPad の電源を切って、すべての電源コードをコンセントから外してください。次に、バッテリー・パックを外し、相互接続ケーブルを外してください。

Antes de quitar una FRU, apague el sistema, desenchufe todos los cables de las tomas de corriente eléctrica, quite la batería y, a continuación, desconecte cualquier cable de conexión entre dispositivos.

Laser compliance statement

Some models of Lenovo computer are equipped from the factory with an optical storage device such as a CD-ROM drive or a DVD-ROM drive. Such devices are also sold separately as options. If one of these drives is installed, it is certified in the U.S. to conform to the requirements of the Department of Health and Human Services 21 Code of Federal Regulations (DHHS 21 CFR) Subchapter J for Class 1 laser products. Elsewhere, the drive is certified to conform to the requirements of the International Electrotechnical Commission (IEC) 825 and CENELEC EN 60 825 for Class 1 laser products.

If a CD-ROM drive, a DVD-ROM drive, or another laser device is installed, note the following:

CAUTION

Use of controls or adjustments or performance of procedures other than those specified herein might result in hazardous radiation exposure.

O uso de controles, ajustes ou desempenho de procedimentos diferentes daqueles aqui especificados pode resultar em perigosa exposição à radiação.

凡未在这里指明的任何控制用法、调整、行为，都会导致严重后果。

Pour éviter tout risque d'exposition au rayon laser, respectez les consignes de réglage et d'utilisation des commandes, ainsi que les procédures décrites.

Werden Steuer- und Einstellelemente anders als hier festgesetzt verwendet, kann gefährliche Laserstrahlung auftreten.

Az itt előírt eljárásoktól, beállításoktól és vezérlésektől eltérni a lézersugárzás veszélye miatt kockázatos!

L'utilizzo di controlli, regolazioni o l'esecuzione di procedure diverse da quelle specificate possono provocare l'esposizione a.

Использование элементов настройки и выполнение процедур иных, чем указано здесь, может привести к опасному радиационному облучению.

Použitie kontrol, úprav alebo iných vykonaní od iných výrobcov, ako je v tomto špecifikované, mohlo by mať za následok nebezpečenstvo vystavenia sa vyžiarovaniu.

本書で指定された内容以外の、お客様による整備、調整、または手順を行った場合、レーザー光の放射の危険があります。

El uso de controles o ajustes o la ejecución de procedimientos distintos de los aquí especificados puede provocar la exposición a radiaciones peligrosas.

Opening the CD-ROM drive, the DVD-ROM drive, or any other optical storage device could result in exposure to hazardous laser radiation. There are no serviceable parts inside those drives. **Do not open.**

A CD-ROM drive, a DVD-ROM drive, or any other storage device installed may contain an embedded Class 3A or Class 3B laser diode. Note the following:

⚠ DANGER

Emits visible and invisible laser radiation when open. Do not stare into the beam, do not view directly with optical instruments, and avoid direct exposure to the beam.

Radiação por raio laser ao abrir. Não olhe fixo no feixe de luz, não olhe diretamente por meio de instrumentos óticos e evite exposição direta com o feixe de luz.

开启时会有激光发射时，请勿直视激光光束，请勿直接查看视觉仪器，并且避免直接接触在激光光束之中。

Rayonnement laser si carter ouvert. Évitez de fixer le faisceau, de le regarder directement avec des instruments optiques, ou de vous exposer au rayon.

Laserstrahlung bei geöffnetem Gerät. Nicht direkt oder über optische Instrumente in den Laserstrahl sehen und den Strahlungsbereich meiden.

Kinyitáskor lézersugár ! Ne nézzen bele se szabad szemmel, se optikai eszközökkel. Kerülje a sugárnyalábbal való érintkezést!

Aprendo l'unità vengono emesse radiazioni laser. Non fissare il fascio, non guardarlo direttamente con strumenti ottici e evitare l'esposizione diretta al fascio.

Открывая, берегитесь лазерного излучения.
Не смотрите на луч, не разглядывайте его
с помощью оптических инструментов, а также
избегайте прямого воздействия лазерного луча.

Keď je laserová jednotka otvorená. Vyhňte sa priamemu pohľadu a nehládte priamo s optickými nástrojmi do lúča a vyhňte sa priamemu vystaveniu lúčov.

開けるとレーザー光が放射されます。光線を見つめたり、光学機械を使って直接見たりしないでください。

Radiación láser al abrir. No mire fijamente ni examine con instrumental óptico el haz de luz. Evite la exposición directa al haz.

Important service information

This chapter presents the following important service information:

- “Strategy for replacing FRUs” on page 16
 - “Strategy for replacing a hard disk drive” on page 17
 - “Important notice for replacing a system board ” on page 17
- “Important information about replacing RoHS compliant FRUs” on page 18

Important:

BIOS and device driver fixes are customer-installable. The BIOS and device drivers are posted on the customer support site:

<http://consumersupport.lenovo.com/>.

Strategy for replacing FRUs

Before replacing parts:

Make sure that all software fixes, drivers, and BIOS downloads are installed before replacing any FRUs listed in this manual.

After a system board is replaced, ensure that the latest BIOS is loaded to the system board before completing the service action.

To download software fixes, drivers, and BIOS, follow the steps below:

1. Go to <http://consumersupport.lenovo.com/>.
2. Enter a serial number or select a product or use Lenovo smart downloading.
3. Select the BIOS/Driver/Applications and download.
4. Follow the directions on the screen and install the necessary software.

Use the following strategy to prevent unnecessary expense for replacing and servicing FRUs:

- If you are instructed to replace an FRU, but the replacement does not solve the problem, reinstall the original FRU before you continue.
- Some computers have both a processor board and a system board. If you are instructed to replace either of them, and replacing one of them does not solve the problem, reinstall that board, and then replace the other one.
- If an adapter or a device consists of more than one FRU, any of the FRUs may be the cause of the error. Before replacing the adapter or device, remove the FRUs one by one to see if the symptoms change. Replace only the FRU that changed the symptoms.

Attention: The setup configuration on the computer you are servicing may have been customized. Running Automatic Configuration may alter the settings. Note the current configuration settings (using the View Configuration option); then, when service has been completed, verify that those settings remain in effect.

Strategy for replacing a hard disk drive

Always try to run a low-level format before replacing a hard disk drive. This will cause all customer data on the hard disk to be lost. Make sure that the customer has a current backup of the data before performing this action.

Attention: The drive startup sequence in the computer you are servicing may have been changed. Be extremely careful during write operations such as copying, saving, or formatting. If you select an incorrect drive, data or programs can be overwritten.

Important notice for replacing a system board

Some components mounted on a system board are very sensitive. Improper handling can cause damage to those components, and may cause a system malfunction.

Attention: When handling a system board:

- Do not drop the system board or apply any excessive force to it.
- Avoid rough handling of any kind.
- Avoid bending the system board and hard pushing to prevent cracking at each BGA (Ball Grid Array) chipset.

Important information about replacing RoHS compliant FRUs

RoHS, The Restriction of Hazardous Substances in Electrical and Electronic Equipment Directive (2002/95/EC) is a European Union legal requirement affecting the global electronics industry. RoHS requirements must be implemented on Lenovo products placed on the market after June 2006. Products on the market before June 2006 are not required to have RoHS compliant parts. If the original FRU parts are non-compliant, replacement parts can also be non-compliant. In all cases if the original FRU parts are RoHS compliant, the replacement part must also be RoHS compliant.

Note: RoHS and non-RoHS FRU part numbers with the same fit and function are identified with unique FRU part numbers.

Lenovo plans to transit to RoHS compliance well before the implementation date and expects its suppliers to be ready to support Lenovo's requirements and schedule in the EU. Products sold in 2005 and 2006 will contain some RoHS compliant FRUs. The following statement pertains to these products and any product Lenovo produces containing RoHS compliant FRUs.

RoHS compliant FRUs have unique FRU part numbers. Before or after the RoHS implementation date, failed RoHS compliant parts must always be replaced with RoHS compliant ones, so only the FRUs identified as compliant in the system HMM or direct substitutions for those FRUs may be used.

Products marketed before June 2006		Products marketed after June 2006	
Current or original part	Replacement FRU	Current or original part	Replacement FRU
Non-RoHS	Can be Non-RoHS	Must be RoHS	Must be RoHS
Non-RoHS	Can be RoHS		
Non-RoHS	Can sub to RoHS		
RoHS	Must be RoHS		

Note: A direct substitution is a part with a different FRU part number that is automatically shipped by the distribution center at the time of the order.

General checkout

This chapter presents the following information:

- “What to do first” on page 20
- “Power system checkout” on page 21

Before you go to the checkout, make sure to read the following important notes:

Important notes:

- **Only certified trained personnel can service the computer.**
- **Before replacing any FRU, read the entire page on removing and replacing FRUs.**
- **When you replace FRUs, use new nylon-coated screws.**
- **Be extremely careful during such write operations as copying, saving, or formatting.** Drives in the computer that you are servicing sequence might have been altered. If you select an incorrect drive, data or programs might be overwritten.
- **Replace an FRU only with another FRU of the correct model.** When you replace an FRU, make sure that the machine model and the FRU part number are correct by referring to the FRU parts list.
- **An FRU should not be replaced just because of a single, unreproducible failure.** Single failures can occur for a variety of reasons that have nothing to do with a hardware defect, such as cosmic radiation, electrostatic discharge, or software errors. Consider replacing an FRU only when a problem recurs. If you suspect that an FRU is defective, clear the error logs and run the test again. If the error does not recur, do not replace the FRU.
- **Be careful not to replace a nondefective FRU.**

What to do first

When you do return an FRU, you must include the following information in the parts exchange form or parts return form that you attach to it:

1. Name and phone number of servicer
2. Date of service
3. Date on which the machine failed
4. Date of purchase
5. Procedure index and page number in which the failing FRU was detected
6. Failing FRU name and part number
7. Machine type, model number, and serial number
8. Customer's name and address

Note for warranty: During the warranty period, the customer may be responsible for repair costs if the computer damage was caused by misuse, accident, modification, unsuitable physical or operating environment, or improper maintenance by the customer.

The following is a list of some common items that are not covered under warranty and some symptoms that might indicate that the system was subjected to stress beyond normal use.

Before checking problems with the computer, determine whether the damage is covered under the warranty by referring to the following list:

The following are not covered under warranty:

- LCD panel cracked from the application of excessive force or from being dropped
- Scratched (cosmetic) parts
- Distortion, deformation, or discoloration of the cosmetic parts
- Plastic parts, latches, pins, or connectors that have been cracked or broken by excessive force
- Damage caused by liquid spilled into the system
- Damage caused by the improper insertion of a PC Card or the installation of an incompatible card
- Improper disc insertion or use of an optical drive
- Diskette drive damage caused by pressure on the diskette drive cover, foreign material in the drive, or the insertion of a diskette with multiple labels
- Damaged or bent diskette eject button
- Fuses blown by attachment of a nonsupported device
- Forgotten computer password (making the computer unusable)
- Sticky keys caused by spilling a liquid onto the keyboard
- Use of an incorrect AC adapter on laptop products

The following symptoms might indicate damage caused by nonwarranted activities:

- Missing parts might be a symptom of unauthorized service or modification.
- If the spindle of a hard disk drive becomes noisy, it may have been subjected to excessive force, or dropped.

Power system checkout

To verify a symptom, follow the steps below:

1. Turn off the computer.
2. Remove the battery pack.
3. Connect the AC adapter.
4. Make sure that power is supplied when you turn on the computer.
5. Turn off the computer.
6. Disconnect the AC adapter and install the charged battery pack.
7. Make sure that the battery pack supplies power when you turn on the computer.

If you suspect a power problem, see the appropriate one of the following power supply checkouts:

- “Checking the AC adapter ” on page 21
- “Checking operational charging” on page 21
- “Checking the battery pack ” on page 22


Checking the AC adapter

You are here because the computer fails only when the AC adapter is used.

- If the power-on indicator does not turn on, check the power cord of the AC adapter for correct continuity and installation.
- If the computer does not charge during operation, go to “Checking operational charging”.

To check the AC adapter, follow the steps below:

1. Unplug the AC adapter cable from the computer.
2. Measure the output voltage at the plug of the AC adapter cable. See the following figure:



Note: Output voltage for the AC adapter pin No. 2 may differ from the one you are servicing.

3. If the voltage is not correct, replace the AC adapter.
4. If the voltage is acceptable, do the following:
 - Replace the system board.
 - If the problem continues, go to “Lenovo G470/G475/G570/G575” on page 27.

Note: Noise from the AC adapter does not always indicate a defect.

Checking operational charging

To check whether the battery charges properly during operation, use a discharged battery pack or a battery pack that has less than 50% of the total power remaining when installed in the computer.

Perform operational charging. If the battery status indicator or icon does not light on, remove the battery pack and let it return to room temperature. Reinstall the battery pack. If the charge indicator or icon is still off, replace the battery pack.

If the charge indicator still does not light on, replace the system board. Then reinstall the battery pack. If it is still not charged, go to the next section.

Checking the battery pack


Battery charging does not start until the Power Meter shows that less than 95% of the total power remains; under this condition the battery pack can charge to 100% of its capacity. This protects the battery pack from being overcharged or from having a shortened life.

To check your battery, move your cursor to the Power Meter icon in the icon tray of the Windows® taskbar and wait for a moment (but do not click it), and the percentage of battery power remaining is displayed. To get detailed information about the battery, double-click the Power Meter icon.

Note: If the battery pack becomes hot, it may not be able to be charged. Remove it from the computer and leave it at room temperature for a while. After it cools down, reinstall and recharge it.

To check the battery pack, follow the steps below:

1. Turn off the computer.
2. Remove the battery pack and measure the voltage between battery terminals 1 (+) and 7 (-). See the following figure:



Terminal	Voltage (V DC)
1	+0 to +14
7	Ground (-)

3. If the voltage is less than +11.0 V DC, the battery pack has been discharged.

Note: Recharging will be continued for at least 3 hours, even though the indicator does not light on.

If the voltage is still less than +11.0 V DC after recharging, replace the battery.

4. If the voltage is more than +11.0 V DC, measure the resistance between battery terminals 5 and 7. The resistance must be 4 to 30 KΩ.

If the resistance is not correct, replace the battery pack. If the resistance is correct, replace the system board.

Related service information

This chapter presents the following information:

- “Restoring the factory contents by using OneKey Recovery” on page 23
- “Passwords” on page 24
- “Power management” on page 25

Restoring the factory contents by using OneKey Recovery

Restore of factory default

The Lenovo G470/G475/G570/G575 computers come with pre-installed OneKey Rescue System. In order to save application files and the initial backed up files of the system, the hard disk in a Lenovo computer includes a hidden partition when it is shipped. If you need to restore the system to the point of your first boot up, just enter Lenovo OneKey Rescue System and run **Restore to factory default**. For details of OneKey Rescue System, see *the User Guide for OneKey Rescue System*.

Note: This will delete all the new data on the system partition (C drive), which is not recoverable. Make sure to back up your critical data before you perform this action.

Using recovery discs

When you replace a hard disk drive in your computer, you are unable to use the pre-installed Lenovo OneKey Recovery and OneKey Rescue. However, you can use the recovery discs that store your backed up data to restore your new hard drive to a previous backup status.

Note: You can create recovery discs by burning the backup image to a CD/DVD as recovery discs. For details of **Create recovery discs**, see *the User Guide for OneKey Rescue System*.

When you use the recovery discs to boot your computer, the system will enter the user interface for system recovery automatically. Please follow the prompt to insert the backup discs to complete the whole recovery process.

Note: The recovery process might take up to 2 hours.

Passwords

As many as two passwords may be needed for any Lenovo computer: the power-on password (POP) and the supervisor password (SVP).

If any of these passwords has been set, a prompt for it appears on the screen whenever the computer is turned on. The computer does not start until the password is entered.

Exception: If only an SVP is installed, the password prompt does not appear when the operating system is booted.

Power-on password

A power-on password (POP) protects the system from being powered on by an unauthorized person. The password must be entered before an operating system can be booted.

Supervisor password

A supervisor password (SVP) protects the system information stored in the BIOS Setup Utility. The user must enter the SVP in order to get access to the BIOS Setup Utility and change the system configuration.

Attention: If the SVP has been forgotten and cannot be made available to the servicer, there is no service procedure to reset the password. The system board must be replaced for a scheduled fee.

Power management

Note: Power management modes are not supported for APM operating system.

To reduce power consumption, the computer has three power management modes: screen blank, sleep (standby), and hibernation.

Screen blank mode

If the time set on the “Turn off monitor” timer in the operating system expires, the LCD backlight turns off. You can also turn off the LCD backlight by pressing Fn+F2.

To end screen blank mode and resume normal operation, press any key.

Sleep (standby) mode

When the computer enters sleep (standby) mode, the following events occur in addition to what occurs in screen blank mode:

- The LCD is powered off.
- The hard disk drive is powered off.
- The CPU stops.

To enter sleep (standby) mode, press Fn+F1.

In certain circumstances, the computer goes into sleep (standby) mode automatically:

- If a “suspend time” has been set on the timer, and the user does not do any operation with the keyboard, the hard disk, the parallel connector, or the diskette drive within that time.
- If the battery indicator is amber, indicating that the battery power is low. (Alternatively, if **Hibernate when battery becomes low** has been selected in the “Power Management Properties” window, the computer goes into hibernation mode.)

To cause the computer to return from sleep (standby) mode and resume the operation, do one of the following:

- Press the Fn key.
- Open the lid.
- Turn on the power switch.

Also, in the following event, the computer automatically returns from sleep (standby) mode and resumes the operation:

- The time set on the resume timer elapses.

Note: The computer does not accept any input immediately after it enters sleep (standby) mode. Wait a few seconds before taking any action to reenter operation mode.

Hibernation mode

In hibernation mode, the following occurs:

- The system status, RAM, VRAM, and setup data are stored on the hard disk.
- The system is powered off.

To cause the computer to enter hibernation mode, follow the steps below:

- If you are using the ACPI operating system and have defined one of the following actions as the event that causes the system to go into hibernation mode, perform that action:
 - Closing the lid.
 - Pressing the power button.

Also, the computer goes into hibernation mode automatically in either of the following conditions:

- If a “hibernation time” has been set on the timer, and if the user does not do any operation with the keyboard, the hard disk drive, the parallel connector, or the diskette drive within that time.
- If the timer conditions are satisfied in suspend mode.

When the power is turned on, the computer returns from hibernation mode and resumes operation. The hibernation file in the boot record on the hard disk drive is read, and system status is restored from the hard disk drive.

Lenovo G470/G475/G570/G575

This chapter presents the following product-specific service references and product-specific parts information:

- “Specifications” on page 27
- “Status indicators” on page 29
- “Fn key combinations” on page 31
- “FRU replacement notices” on page 32
- “Removing and replacing an FRU” on page 33
- “Locations” on page 69
- “Parts list” on page 71

Specifications

The following table lists the specifications of the Lenovo G470/G475/G570/G575 :

Table 1. Specifications

Feature	Description				
Processor	• Intel Huron River Dual Core i7/i5/i3 • AMD Brazos				
Core Chipset	• Intel HM65 • AMD M1				
Bus architecture	<table> <tr> <th>AMD</th><th>INTEL</th></tr> <tr> <td> • 1066MHz DDR3 • UMI • GPP • LVDS • VGA • HDMI • AZALIA • SATA • USB • LPC </td><td> • 1333MHz DDR3 • DMI • FDI • LVDS • VGA • HDMI • AZALIA • SATA • USB • LPC </td></tr> </table>	AMD	INTEL	• 1066MHz DDR3 • UMI • GPP • LVDS • VGA • HDMI • AZALIA • SATA • USB • LPC	• 1333MHz DDR3 • DMI • FDI • LVDS • VGA • HDMI • AZALIA • SATA • USB • LPC
AMD	INTEL				
• 1066MHz DDR3 • UMI • GPP • LVDS • VGA • HDMI • AZALIA • SATA • USB • LPC	• 1333MHz DDR3 • DMI • FDI • LVDS • VGA • HDMI • AZALIA • SATA • USB • LPC				
Graphic memory chip	• ATI Robson XT • Intel intergrated • AMD intergrated				
Display	• 14.0" 16:9, 1366x768 pixels HD/220nit, Glare/White LED/5.2mm wedge type (G470/G475) • 15.6" 16:9, 1366x768 pixels HD/220nit, Glare/White LED/6mm wedge type (G570/G575)				
Standard memory	• DDR3-1066/1333MHz SODIMM socket x 2 (max 4GB per slot)				
CMOS RAM	• INTEL, 512bytes • AMD, 256 bytes				
Hard disk drive	• 2.5" 9.5mm(7mm compatible) SATA II (SATA III capatible), 7200&5400rpm				
Optical drive	• Internal, 12.7mm (ODD dummy ready) • RAMBO, blueray combo				

Table 1. Specifications (continued)

Feature	Description
I/O port	• Stereo Headphone Jack • Microphone Jack • VGA x 1 • HDMI port (selected models only) (G470/G570) • RJ45 x 1 • USB 2.0 x 4 • 5 in 1 media card reader (SD/SD pro/MMC/MS pro/XD) (G470/G570) • 2 in 1 media card reader (SD/MMC) (G475/G575)
MODEM slot	• N/A
Audio	• 1/8" Stereo Headphone Output Jack • 1/8" Microphone Input Jack • Built-in stereo speakers
Video	• CRT port x 1 (on planar), HDMI port x 1 (on planar) (G470/G570)
Ethernet (on the system board)	• 10/100 Mb
Bluetooth	• option
Keyboard	• 6-row Lenovo Keyboard
Touch pad	• Normal type with two buttons
Integrated camera	• 0.3M/2.0M pixels
Battery	• Li-ion battery (6 cells) 2200 mAh
AC adapter	• 90W/65W/40W
Pre-installed operating system	• Win7 Starter/Home Basic/Home Premium/Professional • Free-DOS • Meego (selected models only)

Status indicators

The system status indicators below show the computer status:




Table 2. Status indicators

Indicator	Meaning
■ Caps lock 	White: Caps Lock mode is enabled. You can enter all alphabetic characters (A-Z) in uppercase without pressing the Shift key. To enable or disable Caps Lock mode, press the CapsLk key.
2 Num lock 	White: The separate numeric keypad on the keyboard is enabled. To enable or disable the numeric keypad, press the Num Lock key.
3 Power on 	White: System is enabled. Blinking white: System is in sleep mode. Off: System is in hibernate mode or shut down.

Table 2. Status indicators (continued)

Indicator	Meaning
4 Battery status 	Blinking amber (500ms off/1s on): The remaining power of the battery is less than 5% of its capacity. Blinking amber (100ms off/3.2s on): The battery is being charged with the remaining power between 5% and 20% of its capacity. Amber: The computer is operating on battery power with the remaining power between 5% and 20% of its capacity. Blinking white: The battery is being charged with the remaining power between 20% and 80% of its capacity. White: The remaining power of the battery is more than 80% of its capacity, or the computer is operating on battery power with the remaining power between 20% and 80% of its capacity.
5 Wireless status 	White: Any one of the wireless devices (WLAN/Bluetooth) is enabled. Off: All the wireless devices (WLAN/Bluetooth) are disabled.
6 Drive in use 	White: Data is being read from or written to the hard disk drive or the optical disk drive. When this indicator is on, do not put the computer into standby mode or turn off the computer. Note: Do not move the system while the white drive-in-use light is on. Sudden physical shock could cause drive errors.

Fn key combinations

The following table shows the function of each combination of Fn with a function key.

Table 3. Fn key combinations

Key combination	Description
Fn + Esc:	Turn on/off the integrated camera.
Fn + F1:	Enter sleep mode.
Fn + F2:	Turn on/off the backlight of the LCD screen.
Fn + F3:	Open the interface for the display device switch to select this notebook or an external display.
Fn + F4:	Open the interface for display resolution settings.
Fn + F5:	Open the interface for integrated wireless devices settings (on/off).
Fn + F6:	Enable/Disable the touchpad.
Fn + F8 (G470/ G475):	Enable/Disable the numeric keypad.
Fn + F9:	Start/Pause playback of Windows Media Player.
Fn + F10:	Stop playback of Windows Media Player.
Fn + F11:	Skip to the previous track.
Fn + F12:	Skip to the next track.
Fn + Insert (G570/G575):	Enable/Disable the scroll lock.
Fn + PgUp (G470/G475):	
Fn + PrtSc:	Activate the system request.
Fn + Home:	Activate the pause function.
Fn + End:	Activate the break function.
Fn + PgDn (G470/G475):	Activate the insert function.
Fn + ↑/ ↓:	Increase/Decrease display brightness.
Fn + →/ ←:	Increase/Decrease sound volume.

FRU replacement notices

This section presents notices related to removing and replacing parts. Read this section carefully before replacing any FRU.

Screw notices

Loose screws can cause a reliability problem. In the Lenovo computer, this problem is addressed with special nylon-coated screws that have the following characteristics:

- They maintain tight connections.
- They do not easily come loose, even with shock or vibration.
- They are harder to tighten.
- Each one should be used only once.


Do the following when you service this machine:

- Keep the screw kit in your tool bag.
- Always use new screws.
- Use a torque screwdriver if you have one.

Tighten screws as follows:


- **Plastic to plastic**

Turn an additional 90° after the screw head touches the surface of the plastic part:



- **Logic card to plastic**

Turn an additional 180° after the screw head touches the surface of the logic card:



- **Torque driver**

If you have a torque screwdriver, refer to the "Torque" column for each step.

- Make sure that you use the correct screws. If you have a torque screwdriver, tighten all screws firmly to the torque shown in the table. **Never use a screw that you removed. Use a new one. Make sure that all screws are tightened firmly.**
- Ensure torque screwdrivers are calibrated correctly following country specifications.

Removing and replacing an FRU

This section presents exploded figures with the instructions to indicate how to remove and replace the FRU. Make sure to observe the following general rules:

1. Do not attempt to service any computer unless you have been trained and certified. An untrained person runs the risk of damaging parts.
2. Before replacing any FRU, review "FRU replacement notices" on page 32
3. Begin by removing any FRUs that have to be removed before the failing FRU. Any of such FRUs are listed at the top of the page. Remove them in the order in which they are listed.
4. Follow the correct sequence in the steps to remove the FRU, as given in the figures by the numbers in square callouts.
5. When turning a screw to replace an FRU, turn it in the direction as given by the arrow in the figure.
6. When removing the FRU, move it in the direction as given by the arrow in the figure.
7. To put the new FRU in place, reverse the removal procedures and follow any of the notes that pertain to replacement. For information about connecting and arranging internal cables, see "Locations" on page 69.
8. When replacing an FRU, use the correct screw as shown in the procedures.

DANGER

Before removing any FRU, turn off the computer, unplug all power cords from electrical outlets, remove the battery pack, and then disconnect any of the interconnecting cables.

Attention: After replacing an FRU, do not turn on the computer until you have made sure that all screws, springs, and other small parts are in place and none are loose inside the computer. Verify this by shaking the computer gently and listening for rattling sounds. Metallic parts or metal flakes can cause electrical short circuits.

Attention: The system board is sensitive to, and can be damaged by, electrostatic discharge. Before touching it, establish personal grounding by touching a ground point with one hand or using an electrostatic discharge (ESD) strap (P/N 6405959) to remove potential shock reasons.

Notes:

- The illustrations used in this section are of the Lenovo G570, unless otherwise stated.
- The following procedures about removing and replacing FRUs are the same for the G470&G475&G570&G575.


1010 Battery pack

⚠ DANGER

Only use the battery specified in the parts list for your computer. Any other battery could ignite or explode.

Figure 1. Removal steps of battery pack

Unlock the battery release lever **1**. Holding the battery release lever in the unlocked position **2**, remove the battery pack in the direction shown by arrow **3**.



When installing: Install the battery pack along the slide rails of the slot. Then make sure that the battery release lever is in the locked position.


1020 Dummy card

For access, remove this FRU:

- “1010 Battery pack” on page 34

Figure 2. Removal steps of dummy card

Remove dummy card in the direction shown by arrows **1** **2**.




1030 Optical drive

For access, remove these FRUs in order:


- “1010 Battery pack” on page 34

Figure 3. Removal steps of optical drive

Remove the screw shown in the illustration **1**, and then gently pull the optical drive out in the direction shown by arrow **2** **3**.



Step	Screw (quantity)	Color	Torque
1	M2.5 × 8 mm, flat-head, nylon-coated (1)	Black	2.0kgfcm



1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover


For access, remove this FRU:

- “1010 Battery pack” on page 34

Figure 4. Removal steps of HDD/Memory/CPU/Mini PCI ExpressCard slot compartment cover

Note: Loosen the screws , but do not remove them.

Remove the HDD/Memory/CPU/Mini PCI ExpressCard slot compartment cover in the direction shown by arrow .



1050 Hard disk drive

For access, remove these FRUs in order:


- “1010 Battery pack” on page 34
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37


Attention:

- **Do not drop the hard disk drive or apply any physical shock to it.** The hard disk drive is sensitive to physical shock. Improper handling can cause damages and permanent loss of data.
- Before removing the drive, suggest the customer to backup all the information on it if possible.
- Never remove the drive while the system is operating or is in suspend mode.

Figure 5. Removal steps of Hard disk drive

Remove two screws **1**. Pull the HDD bracket in the direction shown by arrow **2**. Take out the hard disk drive secured in a metal frame **3**.





Step	Screw (quantity)	Color	Torque
3	M2.0 × 4 mm, flat-head, nylon-coated (2)	Black	2.0kgfcm

When installing: Make sure that the HDD connector is attached firmly.


1060 DIMM

For access, remove these FRUs in order:


- “1010 Battery pack” on page 34
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37

Figure 6. Removal steps of DIMM

Release the two latches on both edges of the socket at the same time in the direction shown by arrows **1**, and then unplug the DIMM in the direction shown by arrow **2**.



Note: If only one DIMM is used on the computer you are servicing, the card must be installed in SLOT-0 (**a** : lower slot), but not in SLOT-1 (**b** : upper slot).



When installing: Insert the notched end of the DIMM into the socket. Push the DIMM firmly, and pivot it until it snaps into the place. Make sure that it is firmly fixed in the slot and difficult to be moved.


1070 Fan assembly and Heat Sink assembly

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37

Figure 7. Removal steps of fan assembly and heat sink assembly

Note: Remove three screws **1** and four spring screws **2**.
Unplug the connector in the direction shown by arrow **3**.




When installing: Make sure that the fan connector is attached firmly to the system board.

Step	Screw (quantity)	Color	Torque
1	M2.0 × 4 mm, flat-head, nylon-coated (3)	Silver	2.0kgfcm
2	M2.0 × 3.2 mm, with spring, nylon-coated (4)	Black	2.0kgfcm


Figure 7. Removal steps of fan assembly and heat sink assembly (continued)

Lift the fan assembly and heat sink assembly in the direction shown by arrow 4. Be careful not to damage the connector.



Attention: Do not handle the heat sink assembly roughly. Improper handling can cause distortion or deformation and imperfect contact with components.

Figure 7. Removal steps of fan assembly and heat sink assembly (continued)



When installing:

- Before you attach the fan assembly to the computer, apply thermal grease, at an amount of 0.2 grams, to the **a** part shown in the figure above. Either too much or too less grease application can cause a thermal problem due to imperfect contact with a component.

1080 CPU


For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37
- “1070 Fan assembly and Heat Sink assembly” on page 41

Attention: CPU is extremely sensitive. When you service the CPU, avoid any kind of rough handling.

Figure 8. Removal steps of CPU

Rotate the head of the screw in the direction shown by arrow **1** to release the lock, then remove the CPU in the direction shown by arrow **2**.




When installing: Place the CPU on the CPU socket in the direction shown by arrow **a**, and then rotate the head of the screw in the direction shown by arrow **b** to secure the CPU.

1090 PCI Express Mini Card for wireless LAN

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37

Figure 9. Removal steps of PCI Express Mini Card for wireless LAN



Disconnect the two wireless LAN cables (black, white) in the direction shown by arrows ■, and then remove the screw ■.


Step	Screw (quantity)	Color	Torque
2	M2.0 × 3 mm, flat-head, nylon-coated (1)	Black	2.0kgfcm

In step ■, unplug the jacks by using the removal tool antenna RF connector (P/N: 08K7159), or pick up the connectors with your fingers and gently unplug them in the direction shown by arrows.

Notes: wireless LAN card has 2 cables in step ■.
wireless LAN card in some models may have 3 cables in step ■.

Figure 9. Removal steps of PCI Express Mini Card for wireless LAN (continued)

Remove the card in the direction shown by arrow 3.



When installing:

- In models with a wireless LAN card that has two antenna connectors, plug the black cable into the jack labeled 1, and the white cable into the jack labeled 2 on the card.


1100 Keyboard

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37

Figure 10. Removal steps of keyboard


Remove the screws **1**, **2** on the bottom.



Step	Screw (quantity)	Color	Torque
1	M2.5 × 8 mm, flat-head, nylon-coated (2)	Black	2.0kgfcm
2	M2.5 × 4 mm, flat-head, nylon-coated (1)	Black	2.0kgfcm

Figure 10. Removal steps of keyboard (continued)

Lift the keyboard a little **3**, unlock the FPC connector and then detach the connector in the direction shown by arrows **4** **5**.



When installing: Make sure that the FPC connector is attached firmly and then lock the FPC connector.


1110 Keyboard bezel

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1030 Optical drive” on page 36
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37
- “1050 Hard disk drive ” on page 38
- “1100 Keyboard” on page 47

Figure 11. Removal steps of keyboard bezel


Remove thirteen screws **1**, two screws **2**, two screws **3** and four screws **4** on the bottom.



Step	Screw (quantity)	Color	Torque
1	M2.5 × 8 mm, flat-head, nylon-coated (13)	Black	2.0kgfcm
2	M2.0 × 5 mm, flat-head, nylon-coated (2)	Black	2.0kgfcm
3	M2.0 × 3 mm, flat-head, nylon-coated (2)	Black	2.0kgfcm
4	M2.0 × 2 mm, flat-head, nylon-coated (4)	Black	2.0kgfcm

Figure 11. Removal steps of keyboard bezel (continued)

Remove one screw **5** and detach three FPC connectors in the direction shown by arrows **6**.




Step	Screw (quantity)	Color	Torque
5	M2.5 × 8 mm, flat-head, nylon-coated (1)	Black	2.0kgfcm

When installing: Make sure that all the FPC connectors are attached firmly.

Figure 11. Removal steps of keyboard bezel (continued)

Remove the keyboard bezel in the direction shown by arrows **7**.




1120 Power board and touch inductive panel

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1030 Optical drive” on page 36
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37
- “1050 Hard disk drive ” on page 38
- “1100 Keyboard” on page 47
- “1110 Keyboard bezel” on page 49

Figure 12. Removal steps of power board and touch inductive panel

Remove two screws  and remove the power board .



Notes: The touch inductive panel is fixed on the keyboard bezel.

Step	Screw (quantity)	Color	Torque
	M2.0 × 3 mm, flat-head, nylon-coated (2)	Black	2.0kgfcm

1130 System board

Important notices for handling the system board:

When handling the system board, bear the following in mind.


- Be careful not to drop the system board on a bench top that has a hard surface, such as metal, wood, or composite.
- Avoid rough handling of any kind.
- In the whole process, make sure not to drop or stack the system board.
- If you put a system board down, make sure to put it only on a padded surface such as an ESD mat or conductive corrugated material.

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1020 Dummy card” on page 35
- “1030 Optical drive” on page 36
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37
- “1050 Hard disk drive ” on page 38
- “1060 DIMM” on page 40
- “1070 Fan assembly and Heat Sink assembly” on page 41
- “1090 PCI Express Mini Card for wireless LAN” on page 45
- “1100 Keyboard” on page 47
- “1110 Keyboard bezel” on page 49

Figure 13. Removal steps of system board


Unplug the LCD connector and detach two connectors in the direction shown by arrows ■.



When installing: Make sure that the connectors are attached firmly.

Figure 13. Removal steps of system board (continued)

Remove five screws **2** and detach a connector in the direction shown by arrow **3**.




When installing: Make sure that the connector is attached firmly.

Step	Screw (quantity)	Color	Torque
2	M2.5 × 4 mm, flat-head, nylon-coated (5)	Black	2.0kgfcm

Figure 13. Removal steps of system board (continued)

Remove the system board in the direction shown by arrow **4**.



When installing: When attaching the system board to the base cover, adjust the placement of the wireless radio switch as shown in **b**, and make sure that both of the audio jack and the microphone jack are attached to the holes on the base cover as shown in **a**. Improper placement of the switch or those jacks might cause a damage.

1140 LCD unit

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1020 Dummy card” on page 35
- “1030 Optical drive” on page 36
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover” on page 37
- “1050 Hard disk drive ” on page 38
- “1060 DIMM” on page 40
- “1070 Fan assembly and Heat Sink assembly” on page 41
- “1090 PCI Express Mini Card for wireless LAN” on page 45
- “1100 Keyboard” on page 47
- “1110 Keyboard bezel” on page 49
- “1130 System board” on page 53

Figure 14. Removal steps of LCD unit

Pull out the two antenna cables from the guide hole in the direction shown by arrows **1** and release them from the cable guides in the direction shown by arrows **2**. Remove four screws **3**.





Figure 14. Removal steps of LCD unit (continued)


**When installing:**

- Route the antenna cables along the cable guides. As you route the cables, make sure that they are not subjected to any tension. Tension could cause the cables to be damaged by the cable guides, or a wire to be broken.

Step	Screw (quantity)	Color	Torque
3	M2.5 × 5 mm, flat-head, nylon-coated (4)	Black	2.0kgfcm

Figure 14. Removal steps of LCD unit (continued)

Remove the LCD unit in the direction shown by arrows **4**.




1150 Speakers, bluetooth daughter card and base cover

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1020 Dummy card” on page 35
- “1030 Optical drive” on page 36
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37
- “1050 Hard disk drive ” on page 38
- “1060 DIMM” on page 40
- “1070 Fan assembly and Heat Sink assembly” on page 41
- “1090 PCI Express Mini Card for wireless LAN” on page 45
- “1100 Keyboard” on page 47
- “1110 Keyboard bezel” on page 49
- “1130 System board” on page 53

Figure 15. Speakers, bluetooth daughter card and base cover


Remove four screws **1**, release the speaker cables from the cable guides in the direction shown by arrows **2**, and then remove the speakers.



Step	Screw (quantity)	Color	Torque
1	M2.5 × 5.7 mm, flat-head, nylon-coated (4)	Black	2.0kgfcm

Figure 15. Removal steps of bluetooth daughter card and base cover (continued)


The Bluetooth daughter card is attached to the base cover. Remove the Bluetooth daughter card in the direction shown by arrows **3**.



When installing: Make sure that the connector is attached firmly.

Figure 15. Removal steps of bluetooth daughter card and base cover


Remove the power assembly in the direction shown by arrow **4**.



When installing: Make sure that the power connector is attached firmly.

Figure 15. Removal steps of bluetooth daughter card and base cover (continued)

Remove one screw **5** and then remove the USB assembly in the direction shown by arrow **6**.



When installing: Make sure that the USB connector is attached firmly.

Step	Screw (quantity)	Color	Torque
5	M2.0 × 3 mm, flat-head, nylon-coated (1)	Black	2.0kgfcm

Note: Applying labels to the base cover

The illustrations used in this Note are of the Lenovo G470.


The new base cover FRU is shipped with a kit containing labels of several kinds. When you replace the base cover, you need to apply the following label:

The following labels need to be peeled off from the old base cover, and need to be put on the new base cover.

For models in China:

- a** Windows license label (COA)
- b** ENERGY label
- c** Rating label
- d** PRC CODE label


For the location of each label, refer to the following figure:



For models in other countries or regions:

- a** Bluetooth label (for US/CA/TW/Indonesia)
- b** SIRIM Bluetooth label
- c** SIRIM WLAN label
- d** Bluetooth label (for Brazil)
- e** WLAN label (for Brazil/Israel)
- f** WLAN label (for US/CA/TW/Indonesia)
- g** Windows license label (COA)
- h** Rating label

For the location of each label, refer to the following figure:



For some models, you also need to apply one or two FCC labels. Check the old base cover; if it has one or two FCC labels, find duplicates of them in the label kit and apply them to the new base cover.


1160 LCD front bezel

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1020 Dummy card” on page 35
- “1030 Optical drive” on page 36
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37
- “1050 Hard disk drive ” on page 38
- “1060 DIMM” on page 40
- “1070 Fan assembly and Heat Sink assembly” on page 41
- “1090 PCI Express Mini Card for wireless LAN” on page 45
- “1100 Keyboard” on page 47
- “1110 Keyboard bezel” on page 49
- “1130 System board” on page 53
- “1140 LCD unit” on page 56


Figure 16. Removal steps of LCD front bezel

Remove two screws ■.



Step	Screw (quantity)	Color	Torque
■	M2.5 × 5 mm, flat-head, nylon-coated (2)	Silver	2.0kgfcm

Remove the LCD front bezel in the direction shown by arrows ■.




1170 LCD panel and hinges

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1020 Dummy card” on page 35
- “1030 Optical drive” on page 36
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37
- “1050 Hard disk drive ” on page 38
- “1060 DIMM” on page 40
- “1070 Fan assembly and Heat Sink assembly” on page 41
- “1090 PCI Express Mini Card for wireless LAN” on page 45
- “1100 Keyboard” on page 47
- “1110 Keyboard bezel” on page 49
- “1130 System board” on page 53
- “1140 LCD unit” on page 56
- “1160 LCD front bezel” on page 64

Figure 17. Removal steps of LCD panel and hinges


Remove four screws **1**, and then release the LCD panel. Lift the LCD panel a little and detach the integrated camera connector in the direction shown by arrow **2**. Remove the LCD panel **3**.



Step	Screw (quantity)	Color	Torque
1	M2.5 × 4 mm, flat-head, nylon-coated (4)	Black	2.0kgfcm


Figure 17. Removal steps of LCD panel and hinges (continued)

Remove eight screws **4**, and release the hinges from the LCD panel in the direction shown by arrows **5**.



Step	Screw (quantity)	Color	Torque
4	M2.0 × 3 mm, flat-head, nylon-coated (8)	Black	2.0kgfcm

Detach the connector on the back of the LCD panel in the direction shown by arrow **6**.



Note: The LCD circuit is attached to the LCD panel, and connected with the LCD cable by an FPC connector.

When installing: Make sure that the connector is attached firmly.

1180 Integrated camera


For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1020 Dummy card” on page 35
- “1030 Optical drive” on page 36
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37
- “1050 Hard disk drive ” on page 38
- “1060 DIMM” on page 40
- “1070 Fan assembly and Heat Sink assembly” on page 41
- “1090 PCI Express Mini Card for wireless LAN” on page 45
- “1100 Keyboard” on page 47
- “1110 Keyboard bezel” on page 49
- “1130 System board” on page 53
- “1140 LCD unit” on page 56
- “1160 LCD front bezel” on page 64
- “1170 LCD panel and hinges” on page 65

Figure 18. Removal steps of integrated camera

Note: The integrated camera is stuck on the top center of the LCD cover.

Remove the integrated camera in the direction shown by arrow ■.



When installing: Stick the integrated camera to the top center of the LCD cover and adjust the placement of it to make sure the connector is attached firmly. When replacing the integrated camera, route the connector cable as shown in the figure above.


1190 Antenna assembly and LCD cover

For access, remove these FRUs in order:

- “1010 Battery pack” on page 34
- “1020 Dummy card” on page 35
- “1030 Optical drive” on page 36
- “1040 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI ExpressCard slot compartment cover ” on page 37
- “1050 Hard disk drive ” on page 38
- “1060 DIMM” on page 40
- “1070 Fan assembly and Heat Sink assembly” on page 41
- “1090 PCI Express Mini Card for wireless LAN” on page 45
- “1100 Keyboard” on page 47
- “1110 Keyboard bezel” on page 49
- “1130 System board” on page 53
- “1140 LCD unit” on page 56
- “1160 LCD front bezel” on page 64
- “1170 LCD panel and hinges” on page 65

Figure 19. Removal steps of antenna assembly and LCD cover

Peel off the adhesive tapes securing the antenna boards, release the cables from the cable guide, and then remove the antenna assembly in the direction shown by arrows .




When installing: Route the antenna cables along the cable guides and secure the antenna boards with adhesive tapes. As you route the cables, make sure that they are not subjected to any tension. Tension could cause the cables to be damaged by the cable guides, or a wire to be broken.

Locations


Front view

- Integrated camera
- 2 Wireless module antennas (Select models only)
- 3 System status indicators
- Note:** For the description of each indicator, see “Status indicators” on page 29.
- 4 OneKey Rescue system button
- 5 Power button
- 6 Built-in microphone
- 7 Integrated wireless device switch (Select models only)
- 8 Touchpad
- 9 Memory card slot




Right-side view

- Headphone jack
- 2 Microphone jack
- 3 Optical drive
- 4 USB port
- 5 AC power adapter jack



Bottom and Left-side view

- USB ports
- 2 HDMI port (Select models only) (G470/G570)
- 3 RJ-45 port
- 4 VGA port
- 5 Fan louvers
- 6 Kensington slot
- 7 Hard disk drive (HDD)/Memory/CPU (Central processing unit)/Mini PCI Express Card slot compartment
- 8 Battery latch - spring loaded
- 9 Battery pack
- 10 Battery latch - manual



Parts list

This section presents the following service parts:

- “Overall” on page 72
- “LCD FRUs” on page 77
- “Keyboard” on page 79
- “Miscellaneous parts” on page 84
- “AC adapters” on page 85
- “Power cords” on page 86

Notes:

- Each FRU is available for all types or models, unless specific types or models are specified.

Overall




Table 4. Parts list—Overall

No.	FRU	FRU no.
1	LCD unit (see “LCD FRUs” on page 77.)	
2	Keyboard (see “Keyboard” on page 79.)	
3	PIWG2 LOGIC UPPER-AL W/TP FOR W/HDMI(G570)	31048963
3	PIWG1 LOGIC UPPER-TEXTURE W/TP WO/HDMI(G475)	31048962
3	PIWG2 LOGIC UPPER-TEXTURE W/TP WO/HDMI(G575)	31048964
3	PIWG1 LOGIC UPPER W/TP-HDMI PK090005M50(G470)	31048222
4	PIWG1 POWER BOARD DIS W/FFC 455NI738L01	11013161
4	PIWG2 POWER BOARD UMA W/FFC 455NI738L21	11013162
5	PIWG2 MB DIS 1GVRAM 100LAN W/HDMI(G570)	11013254
5	PIWG2 MB DIS 512VRAM 100LAN W/HDMI(G570)	11013255
5	PIWG2 MB UMA 100LAN W/HDMI(G570)	11013256
5	PAWGC MB DIS 512M 100LAN WO/HDMI-E350(G475)	11013326
5	PAWGC MB UMA 100LanWO/HDMI-AMD E350 1.6GG(G475)	11013279
5	PAWGD MB DIS 1G VRAM 100LAN WO/HDMI-E350I(G575)	11013327
5	PAWGD MB UMA 100LanWO/HDMI-AMD E350 1.6GI(G575)	11013280
5	PIWG1 MB DIS 1GVRAM 100LAN W/HMDI(G470)	11013158
5	PIWG1 MB DIS 512M VRAM 100LAN W/HDMI(G470)	11013159
5	PIWG1 MB UMA 100LAN W/HDMI 4619AB38L01(G470)	11013160
6	CPU assembly, Intel I7-2620M 2.7G 4M 2c J1 PGA processor	102001069
6	CPU assembly, Intel I5-2540M 2.6G 3M 2c J1 PGA processor	102001068
6	CPU assembly, Intel I5-2520M 2.5G 3M 2c J1 PGA processor	102001067
6	CPU assembly, Intel I5-2410M 2.3G 3M 2c J1 PGA processor	102001066
6	CPU assembly, Intel I3-2310M 2.1G 3M 2c J1 PGA processor	102001065
7	PIWG2 CARD READER-15.6 S6751(G570)	31048398
7	PAWGC CARD READER-14 2IN1(G475)	31048408
7	PAWGD CARD READER-15.6 2IN1(G575)	31048406
7	PIWG1 CARD READER-14 455NI838L01(G470)	31048213
8	PIWG1 FAN W/CABLE DC280009BA/D/N/S0	31048220
9	PIWG1 THERMAL MODULE-DIS AT0GL0010ACRU0	31048218
9	PIWG1 THERMAL MODULE-UMA AT0GL0020ACRU0	31048219
9	PAWGC THERMAL MODULE-DIS	31048410
9	PAWGC THERMAL MODULE-UMA	31048411
10	PIWG2 SPEAKER SET-15.6 2W 4OHM(G570)	31048405
10	PIWG1 SPEAKER SET-14 PK23000EQ00(G470/G475)	31048228
10	PIWG2 SPEAKER SET-15.6(G575)	31048405
11	DDRIII 1333 1GB, HMT112S6DFR8C-H9 N0 (Rev Vega/1Gb/44nm)	11012767
11	DDRIII 1333 1GB, RMT3010EF48E7W-1333(Rev. F/1Gb/60nm)	11012634

Table 4. Parts list—Overall (continued)

No.	FRU	FRU no.
11	DDRIII 1333 1GB, SY321NG08HBF (Vega/1Gb/44nm)	11012810
11	DDRIII 1333 1GB, SH564288FH8NWPFSFG(Rev F /1Gb/46nm)	11013083
11	DDRIII 1333 2GB, M471B5773CHS-CH9(Rev C /2Gb/46nm)	11012630
11	DDRIII 1333 2GB, EBJ21UE8BFU0-DJ-F (Rev.F/1Gb/60nm)	11012608
11	DDRIII 1333 2GB, RMT1950MD58E8F-1333(V69A/2Gb/50nm)	11012213
11	DDRIII 1333 2GB, HMT325S6BFR8C-H9 N0 (Rev Vega/2Gb/44nm))	11012197
11	DDRIII 1333 2GB, RMT3020EF48E8W-1333(Rev. F/1Gb/60nm)	11012633
11	DDRIII 1333 2GB, SY321NH08HAF (Vega/2Gb/44nm)	11012809
11	DDRIII 1333 2GB, SH564568FH8NWPFSFG(Rev F /1Gb/46nm)	TBD
11	DDRIII 1333 4GB, M471B5273CH0-CH9 (Rev C /2Gb/46nm)	11011934
11	DDRIII 1333 4GB, HMT351S6BFR8C-H9 N0 (Vega/2Gb/44nm)	11012199
11	DDRIII 1333 4GB, MT16JSF51264HZ-1G4D1 (Rev V69A/2Gb/50nm)	11012320
12	WLAN card, Intel 6250NX MOW M PCIE NB HMC	20002321
12	WLAN card, Intel 6250GX MOW M PCIE NB HMC	20002388
12	WLAN card, Intel 6150NX MOW M PCIE NB HMC	20002484
12	WLAN card, Intel 6150GX MOW M PCIE NB HMC	20002529
12	WLAN card, Intel 1000N MOW M PCIE NB HMC	20002329
12	WLAN card, Cbt BCM4313 MOW M PCIE NB HMC	20002505
12	WLAN card, Liteon AR9285 HB95 BGN MOW NB	20002357
12	WLAN card, Cbt BCM43227 MOW M PCIE NB HMC	20002506
12	WLAN card, Liteon HB97 MOW M PCIE NB HMC	20002525
13	Bluetooth card, Fcn BCM92070 BT2.1 EDR Flash U NB	20002266
13	Bluetooth card, USI BCM92070 BT2.1 EDR Flash U NB	20002326
13	Bluetooth card, CN CSR BC08 BT2.1 EDR ROM U NB	TBD
14	Battery pack, 6 cell 2.2 Ah, Sanyo L09S6Y02 3S2P 48Wh bty(LH)Comm01	121001091
14	Battery pack, 6 cell 2.2 Ah, LG L09L6Y02 3S2P 48Wh bty(LH)Comm01	121001089
14	Battery pack, 6 cell 2.2 Ah, G470 Sony L10N6Y02 48Wh 3S2P Bty	121001056
14	Battery pack, 6 cell 2.2 Ah, SMP/LG L09M6Y02 3S2P 48Wh bty(LH)Comm01	121001094
14	Battery pack, 6 cell 2.2 Ah, Celx/S L10C6Y02 3S2P 48Wh bty(LH)Comm01	121001071
14	Battery pack, 6 cell 2.2 Ah, G470 Sanyo L09S6Y02 48Wh 3S2P Bty(2yr)	121001081
14	Battery pack, 6 cell 2.2 Ah, G470 LG L09L6Y02 48Wh 3S2P Bty(2yr)	121001082

Table 4. Parts list—Overall (continued)

No.	FRU	FRU no.
14	Battery pack, 6 cell 2.2 Ah, G470 Sony L10N6Y02 48Wh 3S2P Bty(2yr)	121001084
14	Battery pack, 6 cell 2.2 Ah, G470 SMP L09M6Y02 48Wh 3S2P Bty(B-2yr)--BAK or LG	121001083
14	Battery pack, 6 cell 2.2 Ah, G470 Celx L10C6Y02 48Wh 3S2P Bty(S-2yr)	121001072
15	PIWG2 LOGIC LOWER 15.6 FOR W/HDMI(G570)	31048403
15	PAWGC LOGIC LOWER 14 FOR WO/HDMI(G475)	31048938
15	PAWGD LOGIC LOWER 15.6 FOR WO/HDMI(G575)	31048939
15	PIWG1 LOGIC LOWER FOR HDMI AP0GL000800(G470)	31048223
16	PIWG1 SD DUMMY CARD-2IN1 FA0GL000X00	31048227
16	PIWG1 SD DUMMY CARD-5IN1 FA0GL000V00	31048226
17	HDD, 250G 5400rpm SATA, WD2500BPVT-24ZEST0 5400RPM 250G	16004852
17	HDD, 250G 5400rpm SATA, Hitachi HTS545025B9A300 250G 9NB	16004060
17	HDD, 250G 5400rpm SATA, Seagate ST9250315AS 250G 9NB	16004186
17	HDD, 250G 5400rpm SATA, Hitachi HTS543225A7A384 5400RPM 250G	16005023
17	HDD, 250G 5400rpm SATA, Seagate ST250LT003 5400RPM 7MM 250G	16005210
17	HDD, 250G 5400rpm SATA, Toshiba MK2565GSX 5400RPM 250G	16004641
17	HDD, 250G 5400rpm SATA, Samsung HM251HI 5400RPM 250G (Brazil)	16004763
17	HDD, 320G 5400rpm SATA, WD WD3200BPVT-24ZEST0 5400RPM 320G	16004853
17	HDD, 320G 5400rpm SATA, Hitachi HTS545032B9A300 320G 9NB	16004059
17	HDD, 320G 5400rpm SATA, Hitachi HTS543232A7A384 5400RPM 320G	16005024
17	HDD, 320G 5400rpm SATA, Seagate ST320LT020 5400RPM 7MM 320G	16005211
17	HDD, 320G 5400rpm SATA, Toshiba MK3265GSX 5400RPM 320G	16004642
17	HDD, 320G 5400rpm SATA, Samsung HM321HI 5400RPM 320G (Brazil)	16004764
17	HDD, 500G 5400rpm SATA, Seagate ST9500325AS 500G 9NB	16004189
17	HDD, 500G 5400rpm SATA, WD5000BPVT-24HXZT1 5400RPM 500G	16004846
17	HDD, 500G 5400rpm SATA, Hitachi HTS545050B9A300 500G 9NB	16004058
17	HDD, 500G 5400rpm SATA, Toshiba MK5065GSX 5400RPM 500G	16004643
17	HDD, 500G 5400rpm SATA, Samsung HM501II 5400RPM 500G (Brazil)	16004765


Table 4. Parts list—Overall (continued)

No.	FRU	FRU no.
17	HDD, 640G 5400rpm SATA, WD6400BPVT-24HXZT1 5400RPM 640G	16004847
17	HDD, 640G 5400rpm SATA, Toshiba MK6465GSX 5400RPM 640G	16004644
17	HDD, 640G 5400rpm SATA, Samsung HM641JI 5400RPM 640G (Brazil)	16004766
17	HDD, 750G 5400rpm SATA, WD7500BPVT-24HXZT1 5400RPM 750G	16004848
17	HDD, 320G 7200rpm SATA, Hitachi HTS725032A9A364 7200RPM320G	16004530
17	HDD, 320G 7200rpm SATA, Seagate ST9320423AS 7200RPM320G 9NB	16004533
17	HDD, 320G 7200rpm SATA, WD WD3200BEKT 7200RPM 320G WD	16005212
17	HDD, 320G 7200rpm SATA, Hitachi HTS723232A7A364 7200RPM 320G	16005027
17	HDD, 320G 7200rpm SATA, Seagate ST320LT007 7200RPM 7MM 320G	16005030
17	HDD, 500G 7200rpm SATA, Hitachi HTS725050A9A364 7200RPM500G	16004531
17	HDD, 500G 7200rpm SATA, Seagate ST9500420AS 7200RPM500G 9NB	16004532
17	HDD, 500G 7200rpm SATA, WD5000BEKT-24KA9T0 7200RPM 500G	16004850
18	ODD, 12.7 Rambo Tray, HLDS GT33N Tray in Rambo	25011474
18	ODD, 12.7 Rambo Tray, PLDS DS-8A5S Tray in Rambo	25011187
18	ODD, 12.7 Rambo Tray, PSN UJ8A0 Tray in Rambo	25011472
18	ODD, 12.7 BD Combo Tray, HLDS CT30N Tray in BD Combo	25011473
18	ODD, 12.7 BD Combo Tray, PLDS DS-6E2S Tray in BD Combo	25011471
18	ODD, 12.7 BD Combo Tray, Optiarc BC-5540H Tray in BD Combo	25011217
18	ODD, 12.7 BD Rambo for G17, PSN UJ240AF Tray in BD Rambo	25011518
18	ODD, 12.7 BD Rambo for G17, Optiarc BD-5740H Tray in BD Rambo	25011517
19	PIWG1 ODD BEZEL BD COMBO AP0GL000A10	31048209
19	PIWG1 ODD BEZEL-RAMBO AP0GL000A00	31048210
20	PIWG2 THERMAL DOOR-15.6	31048404
20	PIWG1 THERMAL DOOR-14 AP0GL000B00	31048224
—	AC adapter (see “AC adapters” on page 85.)	

LCD FRUs

In Lenovo G470/G475/G570/G575, there are following types of LCDs.

- “14.0-in. HD TFT”
- “15.6-in. HD TFT”



14.0-in. HD TFT (G470/G475)

Table 5. Parts list—14.0-in. HD TFT

No.	FRU	FRU no.
1	PIWG1 LCD SCREW RUBBER UP FH0GL000900	31048207
1	PIWG1 LCD SCREW RUBBER LOW FH0GL000A00	31048208
2	PAWGC LCD BEZEL W/CAMERA AP0GL000110	31048936
2	PIWG1 LCD BEZEL W/CMOS HTM AP0GL000100	31048198
2	PIWG1 LCD BEZEL-CMOS TEXTURE AP0GL000200	31048199
3	PIWG1 LCD BRACKET 14 R+L AM0GL0003/400	31048204
4	14.0 HD LED Panel, B140XW01 V8	18004799
4	14.0 HD LED Panel, N140BGE-L21	18004798
4	14.0 HD LED Panel, LP140WH4-TLA1	18004797
4	14.0 HD LED Panel, LTN140AT16-L01	18004796
4	14.0 HD LED Panel, HT140WXB-501	18004795
4	14.0 HD LED Panel, CLAA140WB11A	18004794
5	PIWG1 LVDS CABLE W/CAMERA DC020015T10	31048203
6	PIWG1 CAMERA 2.0M PK400009U00	31048205
6	PIWG1 CAMERA 0.3M PK400009V00	31048206
7	PIWG1 WLAN ANTENNA 14 R+L (G475)	31048202
8	PIWG1 LCD COVER 14-TEXTURE AP0GL000500	31048201
8	PIWG1 LCD COVER 14-IMR AP0GL000400	31048200

15.6-in. HD TFT (G570/G575)

Table 6. Parts list—15.6-in. HD TFT

No.	FRU	FRU no.
1	PIWG1 LCD SCREW RUBBER UP FH0GL000900	31048207
2	PAWGD LCD BEZEL W/CAMERA AP0GM000120	31048937
2	PIWG2 LCD BEZEL FOR W/CAMERA-HTM	31048952
3	PIWG2 LCD BRACKET 15.6 R+L	31048396
4	15.6 HD LED Panel, B156XW02 V2	18003797
4	15.6 HD LED Panel, N156BGE-L21	18004787
4	15.6 HD LED Panel, LP156WH4-TLA1	18004786
4	15.6 HD LED Panel, LTN156AT16-L01	18004785
4	15.6 HD LED Panel, HT156WXB-500	18004783
4	15.6 HD LED Panel, CLAA156WB11A	18004563
5	PIWG2 LVDS CABLE W/CMOS-15.6	31048395
6	PIWG1 CAMERA 2.0M PK400009U00	31048205
6	PIWG1 CAMERA 0.3M PK400009V00	31048206
7	PIWG2 WLAN ANTENNA 15.6 R+L	31048394
8	PIWG2 LCD COVER 15.6-TEXTURE	31048392
8	PIWG2 LCD COVER 15.6-IMR	31048393

Keyboard

Table 7. Parts list—Keyboard
G470/G475:

Language		P/N
Chicony	Bulgarian	25011556
	Czech-Slovakian	25011557
	International English	25011558
	Swiss	25011559
	Slovenian	25011560
	Icelandic	25011561
	Belgian	25011562
	Four Nordic countries	25011563
	Hungarian	25011564
	Hebrew	25011565
	Greek	25011566
	Dutch	25011567
	Japanese	25011568
	Brazilian	25011569
	Arabic	25011570
	German	25011571
	French	25011572
	Russian	25011573
	Traditional Chinese	25011574
	Korean	25011575
	Canadian English&French	25011671
	LA-Spanish	25011583
	Portuguese	25011576
	Thai	25011577
	Turkish	25011578
	Spanish	25011579
	Italian	25011580
	UK English	25011581
	US English	25011582

Table 7. Parts list—Keyboard (continued)

Language		P/N
Dafon	Bulgarian	25011633
	Czech-Slovakian	25011634
	International English	25011635
	Swiss	25011636
	Slovenian	25011637
	Icelandic	25011638
	Belgian	25011639
	Four Nordic countries	25011640
	Hungarian	25011641
	Hebrew	25011672
	Greek	25011673
	Dutch	25011674
	Japanese	25011675
	Brazilian	25011676
	Arabic	25011677
	German	25011678
	French	25011679
	Russian	25011680
	Traditional Chinese	25011681
	Korean	25011682
	Canadian English&French	25011683
	LA-Spanish	25011684
	Portuguese	25011685
	Thai	25011686
	Turkish	25011687
	Spanish	25011688
	Italian	25011689
	UK English	25011690
	US English	25011691
Sunrex	Bulgarian	25011662
	Czech-Slovakian	25011663
	International English	25011664
	Swiss	25011665
	Slovenian	25011666
	Icelandic	25011667
	Belgian	25011668
	Four Nordic countries	25011669
	Hungarian	25011642
	Hebrew	25011643
	Greek	25011644
	Dutch	25011645
	Japanese	25011646
	Brazilian	25011647
	Arabic	25011648
	German	25011649
	French	25011650

Table 7. Parts list—Keyboard (continued)

Language		P/N
Sunrex	Russian	25011651
	Traditional Chinese	25011652
	Korean	25011653
	Canadian English&French	25011654
	LA-Spanish	25011655
	Portuguese	25011656
	Thai	25011657
	Turkish	25011658
	Spanish	25011659
	Italian	25011660
	UK English	25011661
	US English	25011670

G570/G575:

Language		P/N
Chicony	Bulgarian	25012332
	Czech-Slovakian	25012333
	International English	25012334
	Swiss	25012335
	Slovenian	25012336
	Icelandic	25012337
	Belgian	25012338
	Four Nordic countries	25012339
	Hungarian	25012340
	Hebrew	25012341
	Greek	25012342
	Dutch	25012343
	Japanese	25012344
	Brazilian	25012345
	Arabic	25012346
	German	25012347
	French	25012348
	Russian	25012349
	Traditional Chinese	25012350
	Korean	25012351
	Canadian English&French	25012352
	LA-Spanish	25012353
	Portuguese	25012354
	Thai	25012355
	Turkish	25012356
	Spanish	25012357
	Italian	25012358
	UK English	25012359
	US English	25012186

Table 7. Parts list—Keyboard (continued)

Language		P/N
Dafon	Bulgarian	25012399
	Czech-Slovakian	25012400
	International English	25012401
	Swiss	25012402
	Slovenian	25012403
	Russian	25012404
	Icelandic	25012405
	Belgian	25012406
	Four Nordic countries	25012407
	Hungarian	25012408
	Hebrew	25012409
	Dutch	25012410
	Japanese	25012411
	Brazilian	25012412
	Arabic	25012413
	German	25012414
	French	25012415
	Greek	25012416
	Traditional Chinese	25012417
	Korean	25012418
	Canadian English&French	25012617
	LA-Spanish	25012618
	Portuguese	25012619
	Thai	25012620
	Turkish	25012621
	Spanish	25012622
	Italian	25012623
	UK English	25012624
	US English	25012184
Sunrex	Bulgarian	25012419
	Czech-Slovakian	25012420
	International English	25012421
	Swiss	25012422
	Slovenian	25012423
	Icelandic	25012424
	Belgian	25012425
	Four Nordic countries	25012426
	Hungarian	25012427
	Hebrew	25012428
	Greek	25012429
	Dutch	25012430
	Japanese	25012431
	Brazilian	25012432
	Arabic	25012433
	German	25012434
	French	25012435

Table 7. Parts list—Keyboard (continued)

Language		P/N
Sunrex	Russian	25012436
	Traditional Chinese	25012437
	Korean	25012438
	Canadian English&French	25012439
	LA-Spanish	25012440
	Portuguese	25012441
	Thai	25012442
	Turkish	25012443
	Spanish	25012444
	Italian	25012445
	UK English	25012446
	US English	25012185

Miscellaneous parts

Table 8. Parts list—Miscellaneous parts

FRU	P/N
System miscellaneous parts:	
• (a) PIWG1 HDD BRACKET AM0GL000600	31048225
• (b) PIWG1 ODD BRACKET EC0GL000A00	31048211
Cable miscellaneous parts:	
• (c) PIWG2 DC-IN CABLE-15.6	31048400
• (c) PIWG1 DC-IN CABLE-14 DC30100C1/J/R00	31048215
• (d) PIWG2 USB CABLE-15.6 M/B-USB_WIRE	31048399
• (d) PIWG1 USB CABLE-14 DC301009J00	31048214
• (e) PIWG2 BT CABLE	31048401
• (e) PIWG1 BT CABLE DC020015R00	31048216
• (f) PIWG2 TP FFC-15.6 6P 134MM	31048397
• (f) PIWG1 TP FFC-14 NBX0000SJ00	31048212
Note: Italicized letters in parentheses are references to the exploded view in “Overall” on page 72.	

AC adapters

Table 9. Parts list—3-pin AC adapters

FRU	P/N
Delta ADP-65KH BD 20V/3.25A Aadapter	36001929
Liteon PA-1650-56LC Aadapter	36001651
Brazil PA-1650-52LB Aadapter(Brazil)	36001714
Chicony CPA-A065 20V3.25A Aadapter(330PF)	36001943
Delta ADP-90DD BD 20V4.5A Aadapter	36001941
Liteon PA-1900-56LC 20V4.5A Aadapter(330PF)	36001927
Chicony CPA-A090 20V4.5A Aadapter(330PF)	36001942

Power cords

A Lenovo power cord for a specific country or region is usually available only in that country or region:

Table 10. Parts list—3-pin power cords

Region	P/N
CCC • SSD YD-118-1+IEC53RVV+SSD-3-2B-1 1m	145000602
CCC • LINETEK PC323+RVV300/300+LS15 1m	145000600
Argentina • LINETEK LS15+H03VV-F+LP39 1m	145000599
Danmark • LINETEK LS15+H03VV-F+LP-38 1m	145000598
Switzerland • LINETEK LS15+H03VV-F+LP-37 1m	145000597
Brazil • LINETEK LS15 H03VV-F LP26A 1m	145000596
Israel • LINETEK LS15+H03VV-F+LP-41 1m	145000595
UL • LINETEK LP-30B + SPT-2 + LS15 1m	145000594
UL • LINETEK LP-61L+ H03VV-F+ LS15 1m	145000593
UK • LINETEK LP-61L+ H03VV-F+ LS15 1m	145000593
Indian • LINETEK PE-361+ H05VV-F+ LS15 1m	145000592
Italy • LINETEK LS15+H03VV-F+PE-336 1m	145000591
Korea • LINETEK LS15+H05VV-F+LP-E04A 1m	145000590
Australia • LINETEK LS15+H03VV-F+LP-23A 1m	145000589
Taiwan • LINETEK LS15+VCTF+LP-53 1m	145000588
Japan • LINETEK LS15+VCTF+LP-54 1m	145000587
Africa • LINETEK LS15+H03VV-F+PE-364 1m	145000586
CE • LINETEK LP-34+H03VV-F + LS15 1m	145000585
CCC • Longwell LSG-31+RVV300/300+LS-18 1m	145000568
Argentina • Longwell LP-24+H03VV-F+LS-18 1m	145000567
Danmark • Longwell LP-40+H03VV-F+LS-18 1m	145000566

Table 10. Parts list—3-pin power cords(continued)

Region	P/N
Switzerland • Longwell LP-37+H03VV-F+LS-18 1m	145000565
Brazil • Longwell LP-46+H03VV-F+LS-18 1m	145000564
Israel • Longwell LP-41+H03VV-F+LS-18 1m	145000563
UL • Longwell LP-30B+SPT-2 18AWG+LS-18 1m	145000562
UK • Longwell LP-61L+H03VV-F+LS-18 1m	145000561
Indian • Longwell LP-67+BIS+LS-18 1m	145000560
Italy • Longwell LP-22+H03VV-F+LS-18 1m	145000559
Korea • Longwell LP-486+KTLH03VV-F+LS-5 1m	145000558
Australia • Longwell LP-23A+LFC-3R+LS-18 1m	145000557
Taiwan • Longwell LP-71+VCTF+LS-33 1m	145000556
Japan • Longwell LP-54+VCTF+LS-18 1m	145000555
Africa • Longwell LP-39+H03VV-F+LS-18 1m	145000554
CE • Longwell LP-34A+H03VV-F+LS-18 1m	145000553
CCC • Volex LSG-31+RVV300/300+LS-18 1m	145000538
Argentina • Volex LP-24+H03VV-F+LS-18 1m	145000528
Danmark • Volex LP-40+H03VV-F+LS-18 1m	145000534
Switzerland • Volex LP-37+H03VV-F+LS-18 1m	145000524
Brazil • Volex LP-46+H03VV-F+LS-18 1m	145000527
Israel • Volex LP-41+H03VV-F+LS-18 1m	145000526
UL • Volex LP-30B+SPT-2 18AWG+LS-18 1m	145000537
UK • Volex LP-61L+H03VV-F+LS-18 1m	145000605
Indian • Volex LP-67+BIS+LS-18 1m	145000536
Italy • Volex LP-22+H03VV-F+LS-18 1m	145000535

Table 10. Parts list—3-pin power cords(continued)

Region	P/N
Korea • Volex LP-486+KTLH03VV-F+LS-5 1m	145000533
Australia • Volex LP-23A+LFC-3R+LS-18 1m	145000532
Taiwan • Volex LP-71+VCTF+LS-33 1m	145000531
Japan • Volex LP-54+VCTF+LS-18 1m	145000530
CE • Volex LP-34A+H03VV-F+LS-18 1m	145000525

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service.

Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents.

LENOVO GROUP LTD. PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary.

Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk.

Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Trademarks

The following terms are either registered trademarks or trademarks of Lenovo in the United States and/or other countries:

- Lenovo®
- Lenovo logo®
- IdeaPad®
- VeriFace®
- OneKey Rescue® (OneKey Recovery, OneKey Antivirus)
- APS®
- Power Express®
- Energy Management and ReadyComm®

The following terms are trademarks of Microsoft Corporation in the United States, other countries, or both:

- Windows®
- Windows Vista®
- Windows® 7

The following are trademarks of Intel Corporation or its subsidiaries in the United States, other countries, or both:

- Intel®
- Intel® Core™ 2 Duo

Other company, product, or service names may be the trademarks or service marks of others.